

IN THE CLAIMS:

Claim 1 (currently amended): Light guiding blinds (~~40 through 43, 51, 52~~) having at least partly prism-molded toothed upper sides (~~54, 104~~), said prism-molding being provided at least in ~~the~~ a first portion of the blinds disposed close to ~~[[the]]~~ an irradiation area (104) and serving for deflecting daylight, said prism-molded teeth of one prism side showing towards sun incidence and with one reverse prism side showing towards the interior space, and two blind edges each on the sun incidence side forming an incidence level (~~44~~) portion and two blind edges each on the interior space side forming a deflection ~~[[level]]~~ portion, and a blind edge of a lower blind each in the incidence ~~[[level]]~~ portion and a blind edge of an upper blind each in the deflection ~~[[level]]~~ portion forming an angle ( $\alpha_s$ ) relative to ~~the level of the~~ inner blind edges, and sun irradiation impinging from outside being back-reflected at an angle ( $\alpha_R$ ) relative to ~~the level of the~~ outer blind edges in the direction of the outer space, the front side being the sun incidence side, ~~said levels of~~ said blind edges being in parallel relative to each other, characterized in that

- a) the individual prism-molded tooth sides showing towards sun incidence have angles of inclination ( $\beta$ ) relative to the horizontal, ~~[[said]]~~ an angle of inclination ( $\beta_1$ ) being essentially smaller in the area of the ~~irradiation level (44)~~ incidence portion and ~~[[said]]~~ an angle of inclination ( $\beta_2$ ) being larger at larger distance from the ~~irradiation level~~ incidence portion (44), and
- b) the angles of inclination ( $\beta$ ) of at least one of the individual teeth and/or and the tooth sides of ~~the teeth (106, 107)~~ a first and a second tooth showing towards sun incidence ~~either increase continuously or discontinuously or irregularly increases~~ following a concave curve path (47) increasingly ascending starting from the irradiation area towards the interior space, and
- c) at ~~[[the]]~~ an upper side of light guiding blinds (40, 51) back-reflected radiation (~~82~~) is concentrated and a concentration zone (46, 53) is formed near the ~~irradiation level (44)~~ incidence portion, said concentration zone (46, 53), ~~either by rotating the blinds or by using the changed angle of incidence of the sun,~~ is disposed ~~either~~ in front of at least one of blinds (41) in the ~~irradiation level~~ incidence portion (44) ~~and/or and~~ on the underside (53) of an upper blind (~~52~~) behind the ~~irradiation level (44)~~ incidence portion, and
- d) on the upper side of the light guiding blind (51, 40) back-reflected light radiation ~~may be~~ is back-reflected at the individual teeth at an angle ( $\alpha_R < \alpha_s$ ), ~~the~~ wherein a back reflection

angle ( $\alpha_p$ ) into the outer space ~~[[being]]~~ is smaller than the angle ( $\alpha_s$ ) between two blind edges ~~[[each]]~~ of a lower blind in the ~~irradiation level (44)~~ incidence portion and an upper blind in the deflection ~~[[level]]~~ portion.

Claim 2 (currently amended): Light guiding blinds according to claim 1, characterized in that said light guiding blinds are ~~readjusted~~ tilted in a position through which at the upper side of said blinds retro-reflected light radiation ( $\gamma$ ) impinges at an angle  $\gamma < 90^\circ$  on the underside of blinds ( $\beta$ ).

Claim 3 (currently amended): Light guiding blinds according to claim 1, characterized in that said light guiding blinds are manufactured by a rolling process as a flat blind having uniform tooth formation and by subsequent concave/convex molding of the blind the individual teeth are brought into their ascending angular position  $\beta$ .

Claim 4 (currently amended): Light guiding blinds according to claim 1, characterized in that said light guiding blinds include at least one portion ( $\gamma$ ) oriented towards the interior space which, at least vis-à-vis a first portion ( $\alpha$ ), includes flatter tooth angles  $\beta$ .

Claim 5 (currently amended): Light guiding blinds according to claim 1, characterized in that said light guiding blinds ( $\gamma$ ) are S-shaped.

Claim 6 (currently amended): Light guiding blinds according to claim 1, characterized in that said ~~light guiding blinds consist of~~ at least one first portion of said blinds and at least one second portion of said blinds ~~[[which]]~~ serve as light guiding element for light guidance towards the interior space and wherein said first portion consists of at least said first and second teeth ~~two teeth (106, 107)~~, the first tooth ( $\alpha$ ) including on the side facing the sun light a flat angle of inclination  $\beta$ , and at least ~~one further tooth (107)~~ said second tooth including a steeper angle of inclination  $\beta$ , and that at least the sun-irradiated sides of the teeth are concavely arched.

Claim 7 (previously presented): Light guiding blinds according to claim 1, characterized in that said first portions of said blinds consist of at least one single tooth and at least the

sun-irradiated side of said tooth are concavely arched, and the blinds include at least one second light guiding element for light guidance towards the interior space.

Claim 8 (previously presented): Light guiding blinds according to claim 1, characterized in that said light guiding blind upper sides are holograms.

Claim 9 (currently amended): Light guiding blinds according to claim 1, characterized in that on the underside in the area of a portion (54) of blinds (52) is disposed towards the irradiation area, energy converters for short-wave radiation into long-wave radiation and/or into current are provided.

Claim 10 (previously presented): Process of production of light guiding blinds according to claim 1 in a rotary process by feeding carrier material through a pair of rollers having structured surface, characterized in that microstructuring of said carrier material is obtained by means of a sol-gel coating into which either a prismatic-microstructured surface is embossed by a rotary embossing roller or a prismatic-microstructured surface is imprinted by a rotary printing roller, and which before, during or immediately after embossing or imprinting receives at least an initial curing by being fed electromagnetic radiation or by electron bombardment .

Claim 11 (original): Process of production according to claim 10, characterized in that said sol-gel coating is a nanomer.

Claim 12 (original): Process of production according to claim 10, characterized in that said sol-gel coating constitutes a synthesis of a viscous sol having a high solid content on an SiO<sub>2</sub> base, curing after thermal treatment to constitute a vitreous layer.

Claim 13 (original): Process of production according to claim 10, characterized in that the substrate of said sol-gel coating constitutes a synthesis of inorganic-organic nano composites.

Claim 14 (original): Process of production according to claim 10, characterized in that said substrate of said sol-gel coating constitutes a polymerizing nano composite into which nano scale

inorganic particles are incorporated.

Claim 15 (original): Process of production according to claim 10, characterized in that into said substrate of said sol-gel coating precious metal colloids are incorporated.

Claim 16 (original): Process of production according to claim 10, characterized in that said substrate of said sol-gel coatings is formed of polymerizable silanes and cures through photo polymerization under the irradiation of ultraviolet light.

Claim 17 (original): Process of production according to claim 10, characterized in that said substrate of said sol-gel coatings is produced by ceramic nano particles having a high metal oxide content ( $\text{SiO}_2$ ,  $\text{TiO}_2$ ).

Claim 18 (original): Process of production according to claim 10, characterized in that said coatings consist of hydrolyzed methacryl-oxypropyl-trimethoxysilane and said micro structuring is imprinted by an embossing roller.

Claim 19 (original): Process of production according to claim 10, characterized in that said substrate of said sol-gel coatings consists of organically modified alkoxides and nano scale  $\text{SiO}_2$  particles into which prismatic structures  $< 30$  nm are imprinted.

Claim 20 (original): Process of production according to claim 10, characterized in that said substrate of said sol-gel coatings is a metal colloid containing coating.

Claim 21 (canceled).

Claim 22 (original): Process of production according to claim 10, characterized in that said sol-gel coating applied onto said work piece is sprayed, in a second working step, with redistinguishable ITI nano particles and this sprayed-on layer cures under ultraviolet light as a protective layer.

Claim 23 (currently amended): Process of production according to claim 10, characterized in that the prism-molded surfaces are covered with transparent conductive layers ~~in that said layers~~ selected from the group consisting of at least one of  $\text{In}_2\text{O}_3$ ,  $\text{SnO}_2$  and Sb ~~[[are]]~~ sprayed ~~[[with]]~~ at high temperatures onto a hot work piece surface having temperature of more than  $300^\circ\text{C}$ .

Claim 24 (previously presented): Process of production according to claim 10 or 20, characterized in that said prism-molded molding or printing rollers are structured having a low energy surface with self-structuring nano particles so that with a view to repulsion effects a self-purifying surface results on the work piece.

Claim 25 (previously presented): Process of production according to claim 10, characterized in that said prism-molded molding or printing rollers are coated with a lubricant lacquer based on inorganic/organic nano composites.

Claim 26 (currently amended): Light guiding blinds according to claim 1, characterized in that said light guiding blinds include at least one portion ~~(105, 108)~~ oriented towards the interior space which is arch-shaped or plane.